SPECIALIZED ELECTRICIAN TOOLS

01 CORDLESS CABLE CRIMPING & CUTTING TOOL **PZ - 400C**

- Two stage hydraulic system with 32KN.
- OLED display for Easy reading on:
- Battery percentage
- Working times
- Fault code
- Maintenance note
- Crimping and cutting cycle time of 3 - 6 secs

Key Specifications

Rated pressure Stroke:	32KN
Stroke:	40mm
Max cutting:	Ø40mm Cu/Al cable (Non-fine strand & Extra-fine strand)
Crimping range:	Cu 16-400 mm² (Tubular lug)
Time/work:	3 - 6 s (depend on dia of cable)
Voltage/capacity:	18V/4.0Ah
Charging time:	Approx 80mins
Charging Voltage:	AC 100V-240V; 50-60Hz
Package:	Plastic Box
Ambient Temp:	-10°C - 45°C
Weight:	3.9 Kgs (without jaws and battery)
Size of tool:	450 X 81 X 128mm







Standard Accessories

Crimping Head:	1 pc
Cutting Head:	1 pc
Battery:	2 pc
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set
Crimping dies:	16 - 400 mm²

02 CORDLESS CABLE CUTTING TOOL **PZ-32C**

- Replaceable cutting head
- One hand operation
- Special toothed tool head, not easy to break off or flyout after cut
- In-built Safety features
- For cutting Cu/Al cable upto 32mm Dia
- For cutting fine and superfine stranded Cu/Al cables upto 32mm Dia

Key Specifications

Rated pressure:	20KN
Stroke:	29mm
Single Core Cu Cable:	≤ Ø23mm
Four Core Cu Cable:	≤ Ø23mm
Single Core Al Cable:	≤ Ø25mm
Single Core Armoured cu Cable:	≤ Ø32mm
Oil Cabacity:	60ml
Voltage Capacity:	18V/2.0Ah
Charging Time:	40mins
Charging Voltage:	AC 100V-240V; 50-60Hz
Package:	Plastic Box
Weight (with battery):	3.1 Kgs
Size:	438 X 164 X 75mm







Standard Accessories

Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set

03 WIRE PULLER **CX-8010**

The CX-8010, third-generation wire pulling machine, provides an easy solution for both high- and low-voltage cable pulling in concealed walls. It makes your life easier and saving you time and money. The tool is equipped with a powerful brushless motor and gear box that can quickly feed and retract the 30-meter polymer fish tape installed on its drum.



Key Specifications

Volts:	21V
Charging Type:	100 - 240v ~ 50 - 60Hz 2.3A
Charger Mode No.:	HO502102300G01
DC Battery Type:	Makita 4Ah DC
Threading speed:	0-40m/min (0-131ft/m)
Pull Force:	0-880 N (0-198lbs)
RPM:	0-2600RPM
Net Weight:	8 Kgs
Fish Tape length & dimension:	30m (98.5') / 5.8mm (0.22")



04 WALL CHASER **RMC 2535**

RVS Wall chaser RMC 2535 make exceptionally easy, clean and fast the chasing job in walls and partition walls due to its exclusive design and extraordinary performance.

RVS Wall chaser RMC 2535 are light & versatile, the ideal machines to work in places where efficient, robust & reliable tools are required. Its fast and clean cut avoids damaging the walls and waste material at construction sites.

RVS Wall chaser RMC 2535 are used by professional contractors, easing the hard work of embedding wires, conduits and pipes for the electrical, plumbing, heating and air conditioning industries.

Key Specifications

Power:	2000 W
Voltage:	220 - 240V ~ 50-60Hz
Load Speed:	2200 rpm
Weight:	6.5 kg



Standard Accessories

Cutter blade: 25mm as standard / 35mm at Extra cost
Wrench: 1 No
Carbon Brush: 1 set



Site Applications

